

Mtroniks GENESIS SETUP CHART

BRUSHLESS SPEED CONTROL...

FUNCTION



STEP 1 USE WITH PREVIOUS SETTING OR ENTER SET UP
RED LED ON, GREEN LED FLASHING

PREVIOUS SETTINGS **ENTER SETUP HOLD** **EITHER GREEN OR RED LED WILL NOW BE FLASHING ONCE (DEPENDANT ON PREVIOUS SETTINGS)**

NOTE: ENSURE AT EACH STEP TO HOLD THE STICK IN REQUIRED POSITION UNTIL CORRECT COLOUR LED HAS FLASHED THE REQUIRED NUMBER OF TIMES BEFORE CONTINUING TO THE NEXT STEP

		RED	GREEN
STEP 2	BATTERY SELECTION & CUT OFF VOLTAGE 1 FLASH OF EITHER LED	3 CELL LIPO	2 CELL LIPO
STEP 3	RETURN TO NEUTRAL TO CONTINUE SETUP	NICAD/NIMH AUTO SENSING No. OF CELLS	4 CELL LIPO
STEP 4	2 FLASHES OF EITHER LED		
STEP 5	RETURN TO NEUTRAL TO CONTINUE SETUP		
STEP 6	MAX BRAKES 3 FLASHES OF EITHER LED	75%	50%
STEP 7	RETURN TO NEUTRAL TO CONTINUE SETUP	25%	100%
STEP 8	4 FLASHES OF EITHER LED		
STEP 9	RETURN TO NEUTRAL TO CONTINUE SETUP		
STEP 10	ACCELERATION 5 FLASHES OF EITHER LED	FAST	SLOW
STEP 11	RETURN TO NEUTRAL TO CONTINUE SETUP	VERY SLOW	VERY FAST
STEP 12	6 FLASHES OF EITHER LED		
STEP 13	RETURN TO NEUTRAL TO CONTINUE SETUP		
STEP 14	BRAKES 7 FLASHES OF EITHER LED	OFF	ON

THE GENESIS WILL EMIT A SHORT AUDIBLE TONE TO CONFIRM SETUP IS COMPLETE. UNPLUG THE GENESIS FROM THE BATTERY PACK FOR 10 SECONDS BEFORE RE-CONNECTING AND BEGINNING USE.